

11/08/00

jc803 U.S. PTO

J-921 U.S. PTO  
09/707923

11/08/00

<b>UTILITY PATENT APPLICATION TRANSMITTAL</b> (Only for new nonprovisional applications under 37 CFR 1.53(b))	Attorney Docket No.: D/99628	Total Pages:	
	First Named Inventor or Application Identifier		
	Richard Bentley et al.		
	Express Mail Label No..		

<b>APPLICATION ELEMENTS</b> See MPEP Chapter 600 concerning utility patent application contents	<b>ADDRESS TO:</b> <b>Commissioner for Patents</b> <b>Box Patent Application</b> <b>Washington, DC 20231</b>				
<p>1. <input checked="" type="checkbox"/> Fee Transmittal Form (Submit an original, and a duplicate for fee processing)</p> <p>2. <input checked="" type="checkbox"/> Specification (incl. claims) (Total Pages: 11)</p> <p>3. <input checked="" type="checkbox"/> Drawing(s) (35 USC 113) (Total Sheets: 3) <input checked="" type="checkbox"/> Informal <input type="checkbox"/> Formal</p> <p>4. <input type="checkbox"/> Oath or Declaration (Total Pages: ) a. <input type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed) [Note Box 5 below] <input type="checkbox"/> i. <u>DELETION OF INVENTOR(S)</u> Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).</p> <p>5. <input type="checkbox"/> Incorporation By Reference (usable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.</p> <p>6. <input type="checkbox"/> Microfiche Computer Program (Appendix)</p> <p>7. Nucleotide and/or Amino Acid Sequence Submission (If applicable, all necessary) a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (Identical to computer copy) c. <input type="checkbox"/> Statement verifying identity of above copies</p>					
<b>ACCOMPANYING APPLICATION PARTS</b>					
<p>8. <input type="checkbox"/> Assignment Papers (cover sheet &amp; document(s))</p> <p>9. <input type="checkbox"/> 37 CFR 3.73(b) Statement <input type="checkbox"/> Power of Attorney (when there is an assignee)</p> <p>10. <input type="checkbox"/> English Translation Document (if applicable)</p> <p>11. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations</p> <p>12. <input type="checkbox"/> Preliminary Amendment</p> <p>13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized)</p> <p>14. <input type="checkbox"/> Small Entity Statement(s) <input type="checkbox"/> Statement filed in prior application, Status still proper and desired</p> <p>15. <input type="checkbox"/> Certified Copy of Priority Document(s) (If foreign priority is claimed)</p> <p>16. <input type="checkbox"/> Other:</p>					
<p>17. <input type="checkbox"/> If a <b>CONTINUING APPLICATION</b>, check appropriate box and supply the requisite information: <input type="checkbox"/> Continuation <input type="checkbox"/> Divisional <input type="checkbox"/> Continuation-in-part (CIP) of prior application No: /</p>					
<b>18. CORRESPONDENCE ADDRESS</b>					
<input type="checkbox"/> Same as prior application <input checked="" type="checkbox"/> Correspondence address below					
NAME	John E. Beck				
ADDRESS	Xerox Corporation, Xerox Square - 20A				
CITY	Rochester	STATE	NY	ZIP CODE	14644
COUNTRY	U.S.A.	TELEPHONE	+33 476615112	FAX	716-423-5240 or 716-423-2750

UTILITY PATENT APPLICATION TRANSMITTAL - 37 CFR 1.53(b)  
(Executed Attachment to Page 1)

Page 2

Attorney Docket No. **D/99628**

19. ☐ Cancel in this application original claims: \_\_\_\_\_ of the prior application before calculating the filing fee.  
(At least one original independent claim is retained for this filing).

20. ☒ The filing fee is calculated below:

CLAIMS AS FILED, LESS ANY CLAIMS CANCELED BY ABOVE-INDICATED AMENDMENT(S)				
(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
TOTAL CLAIMS (37 CFR 1.16(c))	20 - 20 =	0	X \$ 18	= \$0.00
INDEPENDENT CLAIMS (37 CFR 1.16(b))	3 - 3 =	0	X \$ 80	= \$0.00
MULTIPLE DEPENDENT CLAIMS (IF APPLICABLE) (37 CFR 1.16(d))		ANY - - 0	\$ 270	= \$0.00
BASIC FEE (37 CFR 1.16(a))				\$710.00
TOTAL				= \$ 710.00

21. ☒ The Commissioner is hereby authorized to charge any filing or prosecution fees which may be required, under 37 CFR 1.16, 1.17, and 1.21 (but not 1.18), or to credit any overpayment, to **Xerox Corporation**, Account No. 24-0025. *An additional copy of this form is enclosed.*
22. ☒ This is an authorization under 37 CFR 1.136(a)(3) to treat any concurrent or future reply, requiring a petition for extension of time, as incorporating a petition for the appropriate extension of time.
23. ☐ Amend the specification by inserting before the first line the sentence:  
--This application is a ☐ continuation ☐ continuation-in-part ☐ divisional  
of Application(s) No(s). \_\_\_\_\_, filed \_\_\_\_.
24. ☐ A CIP declaration is enclosed.
25. ☐ Power of Attorney
- a. ☐ The power of attorney appears in the original papers of the enclosed prior application.
- b. ☐ Enclosed is a copy of the declaration and power of attorney from the enclosed prior application.
- c. ☐ A new declaration with power of attorney is enclosed.

**UTILITY PATENT APPLICATION TRANSMITTAL - 37 CFR 1.53(b)**  
(Executed Attachment to Page 1)

**Page 3**

Attorney Docket No.: **D/99628**

26. ☐ The following inventors named in the prior application are deleted per 37 CFR 1.53(b)(1), 1.63(d)(2) and 1.33 (b):
27. ☐ This application is adding one or more inventors under 37 CFR 1.48 to a previously executed application, with an enclosed: petition, fee, newly executed declaration from all inventors, and written consent of the assignee.
28. ☐ This application claims the priority benefit of one or more Provisional Application No(s). and the first sentence of this application has been or will be amended to so indicate.
29. ☐ Priority is claimed from  
(reinsert all previous priority claims for the entire chain of any prior applications).
30. ☐ Other paper(s) enclosed:

Respectfully submitted,

Thomas Zell

Thomas Zell

Signature per 37 CFR 1.33 & 34

Date: *11/6/2000*

Registration No. 37,481

Telephone No. +33476615112

## **DISPLAY FOR RAPID TEXT READING**

### **BACKGROUND OF THE INVENTION**

#### **1. Field of the Invention**

5        This invention relates to a display for the rapid reading of text. In particular, the invention relates to a so-called Rapid Sequential Visual Presentation (RSVP) type display.

#### **2. Description of Related Art**

Referring to Fig. 1, RSVP is a known display technique in which single  
10       words 10 of a document text are presented in their sequential order, one at a time, at a certain rate, at a fixed location 12 on a display 14. This has been demonstrated to provide a significant increase in reading speed, by removing the need for the reader to engage in saccadic activity (i.e. the distinct leaps made by the eye between fixations). Therefore, the reading speed is  
15       increased by avoiding the normal delay of eye movement.

This technique also uses very little screen space, and has been suggested as a display technique for small portable displays.

However, such a technique does not provide the reader with any contextual information which is normally visible when reading a page or  
20       section of text.

For example, when reading normally from a piece of paper or from a screen image of a whole document, the reader can see where he or she is within the page of the document. This contextual information can be useful in helping the reader to get a sense of the text structure which may be important  
25       for understanding a document. It also provides the reader with important navigational cues within the text which can support searching, or re-reading, or judgment about how much of the text has been read relative to how much needs to be read.

Even if the reader is not conscious of viewing a page, or section of text  
30       as a whole, such contextual information is normally available to the eye subconsciously. The lack of this information with the conventional RSVP

technique illustrated in Fig. 1 means that the reading experience is different or un-natural for the reader, because the usual visual spatial information from a page or section of text is not available to the eye.

### **SUMMARY OF THE INVENTION**

5           The invention has arisen out of an appreciation of the above problem that the eye is not presented (consciously or subconsciously) with any context information with conventional RSVP. It would be desirable to provide an RSVP display which can provide the speed-reading advantages of RSVP but also provide the eye with context-based information.

10           Broadly speaking, one aspect of the invention is to provide a display consisting of:

- (a) an RSVP type region in which words (or short phrases) are presented, sequentially in turn; and
- (b) a thumbnail view of a page or section of the text from which the words in the RSVP region originate,
- 15           (c) wherein the thumbnail view is such as to indicate at least an approximate location of the RSVP text within the thumbnail view.

          The term "thumbnail view" is used herein generally to mean a display in which the text is smaller than that in the RSVP region. The scale of thumbnail view may be significantly smaller than the scale in the RSVP region. In one form, the scale of the thumbnail view may be such that the text is not, in fact, legible in the thumbnail view, the location of text being indicated by dots, lines, or other marks or shading which roughly approximate word pattern in the page or section of text.

25           The thumbnail view preferably shows one or more boundaries of the text section or page, to give the reader an indication of the position of the words he is reading. In a particularly preferred form, the thumbnail view is a low-resolution image of a complete document page.

          In one form, the thumbnail view is a stationary view, and a movable cursor or indicator within the thumbnail view indicates the approximate position of the RSVP text. The cursor or indicator moves automatically within

the thumbnail view as the text is presented sequentially in the RSVP region of the display.

In another form, the thumbnail view is presented as a background to the RSVP region, and moves behind or "under" the RSVP region. The position of the thumbnail view relative to the RSVP region indicates the approximate location of the current RSVP text. The RSVP region therefore acts as a magnified window within the thumbnail view. However, since the RSVP region should remain stationary, the thumbnail view moves behind the RSVP region as text is sequentially displayed in the RSVP region.

The invention can therefore enable the speed-reading advantages of RSVP to be realized while providing the reader consciously or subconsciously with additional context information about the location of the text being read. This can be used by the reader as a context or navigation aid. It can also provide a more natural subconscious reading experience to the eye.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

Embodiments of the invention is now described by way of example only, with reference to the accompanying drawings, in which:

Fig. 1 is a schematic illustration of a conventional RSVP display;

Fig. 2 is a schematic perspective view of a display device according to the invention;

Fig. 3 is a schematic block diagram of the display device of Fig. 2;

Figs. 4(a) and 4(b) are schematic diagrams illustrating a first example of display, and

Fig. 5 is a schematic diagram illustrating a second alternative example of display.

### **DETAILED DESCRIPTION**

Referring to Figs. 2 and 3, an RSVP display apparatus 20 is illustrated having a display device 22 mounted therein. The RSVP display apparatus may be portable, and may consist, for example, of a portable document reader, an electronic "book", a portable computer, or other device. The

display device 22 typically consists of an LCD device; as such devices provide low power consumption for portable apparatus. However, the display apparatus 20 is not necessarily portable, and any suitable display device 22 may be used as desired. For example, the display apparatus may be a conventional computer VDU (Video Display Unit).

The apparatus also comprises a memory 24 for storing data representing text to be viewed, and a display controller 26 for generating an image to be displayed and for controlling the display device 22 to generate the image. The text information stored within the memory 24 may, for example be in the form of image data directly representing an image to be viewed, or it may be in the form of text data for processing by the display controller 26 to generate an image.

The apparatus also includes an input device 28 for enabling a user to input control information for controlling the apparatus 20, and in particular the display controller 26. The input device is not shown explicitly in Fig. 1, but may, for example, comprise one or more of a touch sensitive screen, one or more buttons or keys, or a pointing device. The input device may be used to control, for example, the reading rate (i.e. the rate at which the words are presented in turn in an RSVP display), start and stop controls for starting and stopping the RSVP presentation, and navigation controls for enabling the user to locate text desired to be read.

The display controller 26 generates an image which consists of a first RSVP region in which words are presented sequentially in turn, at a controlled rate, for reading by the user. The display controller 26 also generates a thumbnail view showing a page or section of the text from which the RSVP text is being extracted. The following two examples are non-limiting examples of display schemes which enable the user to obtain contextual information about the document, and about the location of the RSVP text within the document.

Referring to Figs. 4(a) and 4(b), in a first example, an RSVP region 30 is generated in a stationary window located towards the center of a displayed image 32. A thumbnail view 34 of a document page is also generated and

placed in the image “behind” or “under” the RSVP region 30. The RSVP region 30 is therefore effectively in a foreground pane of the display, and the thumbnail view 34 is in a background pane of the display (at least relative to said foreground pane in which the RSVP region is located).

5           The thumbnail view 34 moves relative to the RSVP region 30, such that relative position of the RSVP region 30 with respect to the thumbnail view 34 shows the approximate location of the text which is currently being displayed in the RSVP region 30. As the sequence of words in the RSVP 30 region advances at the set reading rate, the thumbnail view 34 moves in the  
10 background of the display, in a similar manner of movement to a movable document carriage of a mechanical typewriter. In effect, the RSVP region 30 acts as a magnified window within the thumbnail view 34; however, since the RSVP region 30 is stationary in the display, the thumbnail view 34 moves relative to the RSVP region to show the location of the text currently being  
15 displayed.

In Fig. 4(a), the RSVP region 30 is displaying the word “rapid” from the top left corner of the document page. In fig. 4(b), the RSVP region 30 is displaying the word “clever” from the middle of the document page.

In the present embodiment, the thumbnail view 34 is a low resolution  
20 rendering of a complete document page. Depending on the resolution of the display device 22, the thumbnail view 34 will typically not itself be legible (or may be poorly legible).

As shown by the thickened line 36, the thumbnail view 34 is generated to have a shadow, or “depth” which is useful for indicating the number of  
25 subsequent pages in the document, or in a chapter or section of the document.

The example shown in Figs. 4(a) and 4(b) can provide a highly intuitive display of the context of the text presented in the RSVP region 30. However, the thumbnail view 34 is limited to being no greater than about a quarter of the  
30 size of the whole image 32, to provide room for the thumbnail view 34 to be moved around the display relative to the RSVP region 30. This may, in some



cases, place undesirable limitations on the display size, or the display quality, when an especially small display device 22 is desired to be used.

In such cases, the alternative example shown in Fig. 5 may be advantageous. In this example, a stationary RSVP region 40 and a stationary thumbnail view 42 are displayed in separate windows or regions of a display 44. The display controller 26 also generates a movable cursor (or other indicator) 46 within the thumbnail view 42, at a position to indicate the location of the word currently displayed in the RSVP region 40. As the sequence of the words presented in the RSVP region 40 advances, the cursor 46 is moved to show the approximate location of each word, and hence provide the user with context information for the RSVP presentation.

In Fig. 5, the RSVP region 40 is shown below the thumbnail view 42. However, it will be appreciated that the RSVP region could be above, or to one side of, or separated further from, the thumbnail view 42, as desired.

In both of the above examples, a thumbnail view is provided in such a manner as to provide context information for the word sequence displayed in an RSVP display. However, the provision of the thumbnail can additionally be used to provide navigation control for the user. By clicking at, or moving a cursor to, a desired location in the thumbnail view, the display controller 26 can be controlled to start the RSVP presentation from that location in the document text. Also, for the first example illustrated in Figs. 4(a) and 4(b), the user may be able to drag the document thumbnail 34 relative to the RSVP region 30, to control the start position for the RSVP presentation.

It will be appreciated that the foregoing description is merely illustrative of preferred embodiments of the invention, and that many modifications or equivalents will be apparent to the skilled man without departing from the scope or spirit of the invention.

## CLAIMS:

1. A display apparatus for displaying a sequential presentation of words from a section of text, comprising:

- a) a display device; and

- b) a display controller for controlling the image displayed by the display device;

wherein the controller is operable to control the display device to generate an image comprising:

- (a) a first region in which words are presented sequentially one after another in time; and

- (b) a thumbnail view of the section of the text from which the words in the first region are being read;

and wherein the thumbnail view is such as to indicate at least an approximate location within the thumbnail view of the text currently presented in the first region.

2. The display apparatus according to claim 1, wherein the display controller is operable to present words, in turn, in said first region, at a controlled presentation rate.

3. The display apparatus according to claim 1, wherein the display controller is operable to generate the display image with the first region maintained at a generally fixed position within the display image.

4. The display apparatus according to claim 1, wherein the display controller is operable to generate an indicator within the thumbnail view, the position of the indicator corresponding to the position in the section of text of the word currently displayed in the first region.

5. The display apparatus according to claim 4, wherein the display controller is operable to move the position of the indicator as the sequence of words in the first region advances.

6. The display apparatus according to claim 4, wherein the indicator is a cursor.
7. The display apparatus according to claim 4, wherein the display controller is operable to maintain the thumbnail view at a generally fixed position within the display.
8. The display apparatus according to claim 1, wherein the display controller is operable to generate the thumbnail view to be larger than the first region, the thumbnail view being located in a first display pane of the image, and wherein said first region is located in a second display pane of the image in front of said first pane, said first region overlapping the thumbnail view.
9. The display apparatus according to claim 8, wherein the display controller is operable to control the position of the thumbnail view relative to the position of said first region, such that the relative position of the thumbnail view is indicative of the location in said section of text of the word currently displayed in said first region.
10. The display apparatus according to claim 9, wherein the display controller is operable to move the position of the thumbnail view relative to said first region as the sequence of words presented in said first region is advanced.
11. The display apparatus according to claim 10, wherein the display controller is operable to maintain said first region at a generally fixed position within the displayed image.

12. A method of generating a display of a sequential presentation of words from a section of text, the method comprising:
- (a) generating a first display region in which words are presented sequentially one after another in time; and
  - 5 (b) generating a thumbnail view of the section of text from which the words in the first region are being read, the thumbnail view being such as to indicate at least an approximate location within the thumbnail view of the text currently being displayed in the first display region.
- 10 13. The method according to claim 12, wherein the sequence of words presented in the first display region is advanced at a controlled presentation rate.
14. The method according to claim 12, further comprising displaying an indicator in the thumbnail view to indicate the location in the section of text of the word currently displayed in said first display region.
- 15 15. The method according to claim 14, further comprising moving the indicator in the thumbnail view as the sequence of words presented in the first display region is advanced.
16. The method according to claim 12, further comprising generating the thumbnail view to be larger than the first display region, the thumbnail view being located in a first display pane, and the first display region being located in a second display pane in front of the first display pane, the first display region overlapping the thumbnail view.
- 20 17. The method according to claim 16, further comprising controlling the position of the thumbnail view relative to the first display region, such that the relative position of the thumbnail view is indicative of the location in said section of text of the word currently displayed in the first display region.
- 25

18. The method according to claim 17, further comprising moving the position of the thumbnail view relative to the first display region as the sequence of words presented in the first region is advanced.
- 5 19. In a display system for displaying a word sequence from a section of text, the words being displayed in sequence one after another in time, the improvement comprising a display of a thumbnail view of said section text, the thumbnail view indicating the position within said section of text of the word currently displayed in said sequence.
- 10 20. The display system according to claim 19, wherein the display system is a rapid sequential visual presentation type display system.

## **ABSTRACT OF THE DISCLOSURE**

A display system uses so called rapid sequential visual presentation (RSVP) in which words are presented one after another in time, in a window for reading by a user. To provide context information, a thumbnail view of the document page or the section of text is also generated, and is used to indicate the location in the section of text of the word currently displayed in the RSVP window. In one example, an indicator is generated within the thumbnail view to show the position, and the indicator is moved automatically as the RSVP sequence advances. In another example, the thumbnail view is positioned in a background display pane behind the RSVP window, and the thumbnail view is moved relative to the RSVP window to indicate the current position in the text.

1/3




Fig. 1




Fig. 2




Fig. 3

2/3




Fig. 4a

Fig. 4b






Fig. 5

